



CINCHSEAL ROTARY SHAFT SEALS FOR PET FOOD APPLICATION








CINCHSEAL OVERVIEW VIDEO

- Leading manufacturer of rotary shaft seals:
 - o Patented, unique, problem-solving seals
 - Used with screw conveyors, mixers, blenders, and other bulk-handling equipment
 - Seals in slurries, powders and semi-liquids
- o **Industries:** food processing, chocolate, bakery, pulp & paper, feed & grain, industrial, chemical, pharmaceutical, goldmine, battery, and others
- Over 25 years in business
 - o Current Customer Base: < 4000 customers in < 50 countries
 - Located in Mount Laurel, NJ
- Used by 2/3 of world's top food and major companies in every processing industry
 - Standard seals for common equipment types
 - Custom seals designed for specific customers, equipment types, materials and applications





LIP & PACKING SEALS (WATCH A VIDEO)


Advantages

- Low-cost alternative
- Have been around for a long time


Disadvantages


- Unable to handle shaft run-outs
- Do not rotate with the shaft
- Allow product leakage
- Facilitate product loss
- Expensive to maintain
- Cause shaft damage
- Enable bearing failure
- Difficult to hygienically clean
- Require long installation
- Product contamination and recall risk













CINCHSEAL VALUE PROPOSITION

Reduce Waste	 Stop process equipment from leaking valuable product Generate savings on material loss and clean-up costs
Lower Maintenance	 Designed to handle up to ¼" [6.35mm] shaft run-out without losing a seal on the shaft Protect gearboxes, bearings and shafts from damage
Ease of Installation and Hygienic Cleaning	 No need to remove bearings or drive units and do mechanical adjustments due to innovative split design Easily assemble/disassemble for wash-downs between batches
Increase Productivity	 Longer functional life than traditional lip or packing seals Avoid unplanned production downtime
Risk Management	 Prevent product recalls, cross-contamination, and foreign material migration USDA- and FDA-certified sealing products



FEATURES & BENEFITS

CinchSeal's Clean-In-Place (known as CIP) seals are run-out tolerant rotary shaft seals that make the need for processing equipment replacement far less likely as they solve problems associated with traditional lip seals and mechanical packing.

One-year ROI of up to 10x - 35x

Features	Benefits
Rotating Drive Elastomer and Rotors Design	Protects bearings, gearboxes, and shafts from damage
Tolerance for up to 0.250" [6.35mm] Shaft Dynamic Run-out	Prevents cross-contamination, foreign material migration, product leakage and recalls
Self-Adjusting, Abrasion-Resistant Sealing	Eliminates unscheduled downtime, maintenance, and lost productivity
All C.E.M.A. Standard and Metric Sizes	Designed for C.E.M.A. standard and metric screw conveyor and bulk-handling equipment
Innovative Split CIP Design	 Requires no removal of bearings or drive units Allows for hygienic cleaning between batches Enables easy installation and maintenance
FDA-Certified Rebuild Kits	Reduces the total cost of ownership, replacing soft internal components, without compromising the seal
Custom-Tailored to Any Machinery	With custom drawings, perfectly fits on any standard or non- standard new and existing equipment
Available USDA-Certified Models for Dairy, Meat, and Poultry Applications	Provides a hygienic sealing solution for highly regulated industries





PET FOOD EQUIPMENT

- Cookers
- Ribbon Blenders
- Screw conveyors(Horizontal and Incline)
- Augers
- Paddle Mixers
- Bucket Elevators
- Rotary Airlocks









OUR PET FOOD CUSTOMERS

- **O Cargill Animal Nutrition**
- Diamond Pet Foods
- Kelly Foods
- Mars Pet Foods
- Nestle Purina Petcare
- Royal Canin
- Smithfield Foods
- Sunshine Mills
- Tyson Animal Foods





















PET FOOD ROI

ISSUE

- There was a product leakage at the shaft of the mixer at a major pet food manufacturing company.
- The company was losing valuable product.
- In addition, it required extra maintenance and associated expenses to fix the leakage problem on the on-going basis.

SOLUTION

- Switching to CinchSeal's 9700 split stainless-steel rotary shaft seals not only eliminated pet food product loss but also reduced downtime.
- The 9700 series' high performance and long life have provided a documented ROI **\$10,400 per year.**

CINCHSEAL CONVERSIONS









MEAT & POULTRY CERTIFICATE

- USDA certified for Meat and Poultry processing applications
- This Clean-In-Place split design enables fast installation - no removal of bearings or drive units and hygienic wash-downs between batches
- Result eliminates product batch crosscontamination and product recalls





APPLICATIONS








CINCHSEAL ASSEMBLY


5 PARTS:

- Metal End Plate
- Metal Housing
- Elastomer Boot
- 2 PTFE Rotor Cups






CINCHSEAL ASSEMBLY





1). SILICON ELASTOMER

- The elastomer boot grips and seals the shaft without damaging or wearing the shaft. It drives the wearable PTFE seal faces
- The silicone elastomer can withstand temperatures up to 425 degrees °F
- The standard elastomer is made from a "FDA-approved" silicone that handles 95% of industrial applications in the field
- The elastomer material can also be made from VITON, AFLAS and EPDM for harsher chemicals






2). PTFE ROTOR CUPS

- The PTFE stators and rotor cups are made from a mineral-filled PTFE
- Depending on the shaft rotating speeds, the PTFE can be blended with certain minerals to reduce the coefficient of friction at the PTFEmetal interface
- The rotor cups are also FDA approved for indirect food contact and can be USDA certified for sealing in meat, poultry, and dairy


3). METAL PARTS

• Seal housings and end plates are available in aluminum, polypropylene, and 304ss or 316ss, depending on application requirements





SEAL CROSS-SECTION





AIR PURGE IN 5-8 PSI HIGHER THAN PROCESS **AIR PURGING** DNISUDH END PLATE INBOARD STATOR PLATE AIR PATH DUT AIR PATH DUT 111 111 HB. BOOT -D-RING ROTOR CUP-ROTOR CUP



WHY WE AIR PURGE THE SEALS



Creates a higher pressure in the seal chamber to form a natural air barrier that keeps product out of the seal



Develops a force that pushes the rotating faces outward against the stationary faces and creates a tighter seal



Cools the rotating seal faces by reducing temperature caused by friction





SPECIFICATIONS



Silicon And PTFE Internal Parts Are Good Up To 425 °F - Higher Temperature Applications Are Possible



 Up To 45 Psi Operating Pressure
 Purge Seal With 5 To 7 Psi Of Air Above Operating Vessel Pressure For Optimum Performance

· Up To 28" Of Vacuum



Typical Flow Rate Is Less Than 1 CFM With Air Regulator Set At 5 Psi



Maximum Surface Speed -Approximately 270 Ft/Min (5" Shaft @ 200 Rpm, Some Applications Run Up To 400 Rpms)



HOW TO INSTALL THE SEAL VIDEO

















WHY SWITCH TO CINCHSEAL – WATCH A VIDEO

- **Cost Savings:** Eliminates product waste, unscheduled maintenance costs and downtime, premature bearing failure, shaft damage, and reduces energy consumption
- No Damage to Shafts: CinchSeal's unique design protects rotating shafts from being scored or damaged
- Run-out: Can handle up to ¼" [6.35mm] shaft run-out without losing a seal on a shaft
 - Health and Safety: Prevents powder and dust leakages that can cause hazardous work environments and explosions
- Clean-In-Place Design: Allows for hygienic clean-up between product batches
- Proven ROI: One-year ROI of up to 10x 35x